

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International publication date
28 April 2005 (28.04.2005)

PCT

(10) International publication number
WO 2005/037632 A1


- (51) International patent classification⁷: B62D 29/00
- (21) International application number: PCT/EP2004/011555
- (22) International filing date: 14 October 2004 (14.10.2004)
- (25) Language of filing: German
- (26) Language of publication: German
- (30) Data relating to the priority:
103 48 418.3 14 October 2003 (14.10.2003) DE
- (71) Applicant (for all designated states except US): BEHR GMBH & CO. KG [DE/DE]; Mauserstrasse 3, 70469 Stuttgart (DE).
- (72) Inventors; and
(75) Inventors/Applicants (US only): FEITH, Thomas [DE/DE]; Astenstrasse 9/2, 70825 Korntal-Münchingen (DE). MERKLE, Christian [DE/DE]; Stockwiesenweg 2, 73655 Plüderhausen (DE). WOLF, Walter [DE/DE]; Steinbacher Strasse 34/1, 71570 Oppenweiler-Zell (DE).
- (74) Joint Representative: BEHR GMBH & CO. KG; Intellectual Property, G-IP, Mauserstrasse 3, 70469 Stuttgart (DE).
- (81) Designated states (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY,

[continued on next page]

As printed

(54) Title: COMPOSITE PART, ESPECIALLY CROSS MEMBER

(54) Bezeichnung: VERBUNDBAUTEIL, INSBESONDERE QUERTRÄGER



(57) Abstract: The invention relates to a composite part, especially a cross member between the A columns of a motor vehicle. Said composite part comprises an open metal profile (2) and a channel (3) disposed therein, at least partially constituted of a plastic material and extending along the metal profile (2). An insert part (4, 22) produced from a plastic material is fastened on the wall of the metal profile (2) in such a manner that a retaining contour (10) configured on an opening (11) in the wall of the metal profile (2) and shaped from said profile undercuts the plastic material of the insert part (4, 22) pressed into the contour, thereby providing the channel (3) with a wall and/or mechanically stabilizing it.

[continued on next page]

BZ, CA, CH, CN, CO, CR, CU, CZ, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

Declaration under Rule 4.17:

- of inventorship (Rule 4.17(iv)) for the following designation
US

Published:

- with International Search Report.
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(84) Designated states (unless otherwise indicated, for every kind of regional protection available): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For an explanation of the two-letter codes and the other abbreviations, reference is made to the explanations ("Guidance Notes on Codes and Abbreviations") at the beginning of each regular edition of the PCT Gazette.

(57) Zusammenfassung: Ein Verbundbauteil, insbesondere Querträger zwischen A-Säulen eines Kraftfahrzeuges, umfasst ein offenes Metallprofil (2) und einen in diesem angeordneten, zumindest teilweise aus Kunststoff gebildeten, längs des Metallprofils (2) verlaufenden Kanal (3), wobei zur Bildung einer Wandung und/oder mechanischen Stabilisierung des Kanals (3) ein zumindest teilweise aus Kunststoff gefertigtes Einlege teil (4,22) derart an der Wandung des Metallprofils (2) befestigt ist, dass eine an einer Öffnung (11) in der Wandung des Metallprofils (2) aus diesem ausgeformte Haltekantur (10) den in diese eingepressten Kunststoff des Einlege teils (4,22) hinterschneidet.